



IEVOLI SHUTTLE

S/V Rec-oil "IEVOLI SHUTTLE"

THE SHIP IS A SUPPLY VESSEL, DESIGNED TO GIVE ASSISTANCE TO OFF SHORE UNITS IN MED, BLACK AND CASPIAN SEA.

THE SHIP IS DESIGNED TO CARRY:

- DISINFECTED LIQUID SEWAGE
- SEWAGE MUD
- FRESH WATER
- GAS-OIL (FLASH POINT ABOVE 60 DEGREES)
- OIL RECOVERY SHIP

DEDICATED TANKS WITH DEEP-WELL PUMPS ARE INSTALLED.

THE SHIP IS ARRANGED WITH DOUBLE BOTTOM AND DOUBLE SKIN IN CARGO AREA, TWIN SCREW / TWIN ENGINE ARRANGEMENT, BOW THRUSTER, BULBOUS BOW AND FORWARD SUPERSTRUCTURE.

THE SHIP IS REINFORCED FOR NAVIGATION IN BRASH ICE AND TO OPERATE WITH COLD CLIMATE.

AIR CONDITIONING ACCOMODATION FOR 10 CREW IT IS ARRANGED.

MAIN DESCRIPTION

Built : Oct. 2009

Builder : SELAH Shipyard – Tuzla (Turkey)

Owner : Marnavi S.p.A. - Napoli

Classification : Rina Class

RINA C 또, Supply Vessel, oil recovery ship, Special navigation – Mediterranean, Black and Caspian Sea, Ice class 1B, Clean Sea,

Clean air, in water survey.

Port of registry : Naples n. 559 Flag : Italian Rina Number : 86826 IMO Number : 9564437 Call Sign : I.I.W.C.2 Certificates : SOLAS 74 Certificates, Marpol (73/78 and amendments), LSA International Rules, Load

Line Convention 69, Telecommunication / Radio International Convention.

MAIN DIMENSIONS

GRT : 532 tons NET : 159 tons : 45,85 m Loa : 42.85 m Lbp : 9.97 m Breath Moulded Summer Load draft : 2.80 m Depth Moulded : 4.00 m Light Ship Weight : 612 tons

Deadweight : 350 tons (at summer draft)

Deck Cargo Area : 2 x Containers 20"

Deck Cargo strength : 2 t/m²

HULL AND SUPERSTRUCTURE

STEEL PLATES FOR HULL AND SUPERSTRUCTURE OF "A" GRADE.
BULB PROFILES AND FRAMES/LONGITUDINAL ALSO OF "A" GRADE.
THE VESSEL IS ARRANGED WITH:

- DOUBLE HULL
- FORE PEAK FOR BALLAST.
- TRANSVERSAL COFFERDAM BETWEEN GAS-OIL AND MUD TANKS AND BETWEEN SEWAGE/FRESH WATER.
- TWO SPADE RUDDERS.
- . CENTRAL SKEG ON THE AFT.
- FENDERS (HALF PIPE TYPE) IN THE PARALLEL MID-BODY AND ON THE AFT.

PERFORMANCES

Speed : 10 knots

Consumptions (80%) : About 240Kg/h (Diesel Oil)

REC-OIL EQUIPMENT

REC-OIL CAPACITY : 530 m3 (multipurpose tanks)

INFLATABLE OIL BOOM : 200 mt.

SKIMMERS : Hydraulic Skimmers for Oil Recovery

Transfer

SWEEPING ARMS : In Both Sides

DISPERSANT : Chemical Dispersant of Approved Type

OIL TRANSFER PUMPS : Fitted

AND EVERYTHING NECESSARY FOR THE EMERGENCY RECOIL OPERATIONS.

CAPACITIES

Fresh water : $100 \text{ m}^3 - 2x50$ Sewage Mud : $88 \text{ m}^3 - 2x44$ Gasoil ($Pf > 60^\circ$) : $178 \text{ m}^3 - 2x89$

Recovery oil : 530 m³ (multipurpose tanks)

Sewage : $160 \text{ m}^3 - 2x80$

344 m³ Ballast 11 m² Fresh water (for ship) Gasoil (for ship) 32 m² Dirty Oil : 3.60 m³ Sludge : 2.70 m³ Bilge : 3,60 m³ Oily bilge Tank : 5,21 m³ Grey water : 4,10 m³

MACHINERY

Main engine's : 2 x 559 Kw

Builder : CATERPILLAR - Type: C32 ALERT

Shafting : 2 shafts x 4 blades propellers fix pitch

type/each

Generator's : 2 x 150 Kw SCANIA Set

Emergency Batteries 15 Kw

Bow thruster : Bow thruster of fixed pitch type, 4 blades,

driven by an hydraulic motor fed by an hydraulic pump driven by one of two main

engines, 80Kw - 1,5 tons

Rudder's : 2 x "Spade" type

Service compressor: 2 x ATLAS Copco 8,5 bar, 5kw, 40m³/h

Air Draier : 1 x ATLAS Copco

OTHER MACHINERIES INSTALLED IN ENGINE ROOM

2 x Reverse Gearboxes, each with clutch and stand-by hydraulic

2 x Fresh water circulation pump, one stand-by.

1 x General service bottle, 300 l/8 bar.

1 x Bilge pump, as per Rules and one LP GS pump.

1 x Fire pump, (45m³/h, 6 bars).

1 x General Service pump (identical to fire pump) of HP type.

1 x Ballast pump, 100m³/h x 30 mWG.

1 x Gas-oil Purifier with pump.

1 x Gas-oil Transfer pump.

1 x Oil water separator.

One diesel driven pump is on board for emergency service.

Each cargo system is arranged with manifold on deck and valves manually operated.

Level indicators, one per cargo tank, above Main deck.

EQUIPMENTS INSTALLED IN THE FORE EQUIPMENT ROOM

- Hot water boiler (250l) with 3 x 6 electric heaters + circulating pump.
- Emergency fire pump, as per Rules, driven by a diesel engine, portable type.
- One Supply and one exhaust fan.
- Sewage treatment unit.
- Steam generator unit GMT12 (84 Kw)
- Fresh water unit (Calorifier + Hydrophor + Sterilizer)

ACCOMODATION

Cabins : 2 x 1 bed + 4 x 2 beds

Mess room : Fitted
Galley : Fitted
Laundry : Fitted
Hospital : Fitted

DECK EQUIPMENT

Capstan / Windlass : 2 x 3 ton (stern) + 2 x 3 ton windlass /

capstan

Crane : 1 x 2 ton at 10m

F.R.B. : 1 x 6 persons, Length: 4,45m, Eng: 25 Hp

Life Rafts : 2 x 10 pers. RFD

NAVIGATION EQUIPMENT

Radar X band : CONSILIUM SELUX ST-250, 19 1" TFT

- (ARPA function)

Radar S band : CONSILIUM SELUX ST-340, 12ft

(ARPA function)

GPS : SAAB R4 DGPS Echo-sounder : SKIPPER – GDS 101

GMDSS : Inmarsat C – SAILOR 150W SSB/DSC

(Area A1+A2+A3)

SSAS : 403000SSA – 00500 SAILOR mini-C

SART : 2 x SART SAILOR SART II
Speed log : CONSILIUM SAL R1a

Speed log : CON: Wind Speed/Direction : DEIF

Gyro pilot : SPERRYNAVIPILOT 4000

Navtex : ICS NAVTEX NAV 7
Gyro compass : SPERRY NAVIGAT X MK1 (type: G-

TML)

AIS : SAAB R4 AIS

AIS : SAAB R4 AIS

LRIT : (included in GMDSS)

Magnetic Compass : SPERRY NAVIPOL 1

Radio VHF : 2 x SAILOR RT5022 DSC

Radio VHF Portable : 3 x SAILOR 40352B VHF Portable (Ship use) : 2 x SAILOR sp3530 – Intrinsically

(Silip use) . ZX

Inmarsat C : 2 x SAILOR TT3000E

EPIRB : SAILOR TT4062-D (406Mhz)

Weather Chart Plotter : FURUNO
Satellite Phone : Inmarsat C
Satellite Fax : Inmarsat C

P.C. : Fitted (Printer, Scanner, Copies

machines)


OTHER INFORMATION


Frigo Capacities : Domestic Type. Freezers: 2 x 220lt,

Refrigerators: 2 x 220lt

This specification is subject to alteration without prior notice

Ievoli Shuttle - Rec-oil Supply Vessel





Whilst care has been taken in the preparation of this document, the data and/or information referred to herein are purely indicative and are not contractually binding. They must be checked with reference to the specific operations and are subject to change. No liability is accepted by the owners for any errors which may exist in this document.



